

QUOTATION

Deep-drawing vacuum-packing machine MULTIVAC R 530 MC



1. Specification

Formats	:	2x2
Length of drawing	:	198 mm
Depths of drawing	:	max. 50 mm
packing	:	rigid film
bottom film	:	465 mm (+4/+2 mm)
Top film	:	450 mm (+1/-1 mm)
Productivity	:	6 – 8 tacts/min
Dosage	:	no
Gas	:	yes
Voltage	:	3 ph 400V /50Hz, N, I=28 A P=13 kW

Compressed air	:	min. 6 bar Supplying pipeline 1"
Water	:	100-150 liters/hour, 15° C max ½" input
Work-shop	:	air-conditioned

2. Parameters

Machine

- Length 6500mm
- Width 1100mm
- Height 2000mm
- Tools distance - 2 150mm
- 2 x 4- point lifting system
- Transport chain made of stainless steel
- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives for rigid film

1 section for tranverse cutting

for rigid film

1 taking-out band

4: Pumps

VFS 220.80 (01)
220 m³

5: Tools

Vario-tools

Base tool

Film width	465 mm
Length of drawing	198 mm
Max.depth of drawing	50 mm
Appropriate for flexible films	

Vario 1

2 bands, 2 row, = 4 packings/tact

Packing dimensions :

Form dimensions : L x B = 195.0 x 82.0 mm

Outside dimensions : L x B = 210.0 x 100.0 mm

