

QUOTATION

MULTIVAC R 175 SKIN-PACK THERMOFORMER



1. Specification

format	:	3x1
Length of drawing	:	265 mm
Depth of drawing	:	max 22 mm
packing	:	rigid film
bottom film	:	422 mm (+1/-0 mm)
top film	:	422 mm (+1/-0 mm)
Productivity	:	6 -8 Tacts
Voltage	:	400V /50Hz, N, P= 16,5 kW
Compressed air	:	7÷10 bar
Water	:	80-100 liters/hour, 15° C max. 1,5÷4,5 bar ½" input
Work-shop	:	air-conditioned

2. Parameters

Machine

- Length 6 500 mm
- Width 1 100 mm
- Height 2 100 mm
- Transport chain made of stainless steel
- Forming and sealing systems
- Preliminary heating of the bottom film
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- protective devices according current standards
- made of stainless steel

3. Accessories

1 section for tranverse cutting

2 section for longitudinal cutting

2 devices for rolling of waste bands

4: Pumps

1 vacuum pump outside the machine - not included in delivery

Busch 160 m³

400 V 50 Hz

5: Tools

Base tool

Film depth	422 mm
Length of drawing	265 mm
Max.depth of drawing	22 mm
Appropriate for rigid film	

Vario1

3 bands, 1 row = 3 packings/tact

With pad for forming and sticking sections

Dimensions of packing:

Format dimensions: L x B = 250.0 x 110.0 mm

Outside dimensions : L x B = 265.0 x 127,0 mm

