

QUOTATION

FESSMANN TURBOMAT 3000 2W - HD

Combined Universal Smokehouse for thermal treatment of food



Single row system

Capacity for 2 smoke trolleys, batch-type, with following maximum outside dimensions of each trolley: (Width x Length x Height in cm): 104 x 102 x 198 (H) cm;
Maximum length of the smoking stick 100 cm

Control panel: MC2

Heating: **High pressure steam 8 bar, 74 kW;**

Adjustable air circulation

Pneumatically controlled fresh air-, exhaust air- and smoke damper;
cleaning: foam cleaning;

Cooking and humidification: Low pressure steam 0.5 bar

Installation dimensions in cm

Dimensions	Unit	2W steam
Base width	cm.	151

Base depth	cm.	237
Corpus height (without el.motor height and pipes)	cm.	250
Minimum height of the workshop	cm.	304
Recommended height of the workshop	cm.	320
Trolley dimensions HxWxD	cm.	198x104x102 cm

Accessories:

Set of blades made of special steel for the control board with width 325 mm (with smoke-generator RZ325)

Smoke feeding: on the right side

Without after-burning system

Installation on ready made floor;

Voltage: 230/400 V with N

Frequency: 50 Hz

Smoke-generator RZ 325



Smoke generator RZ325 system with 3 smoke densities:

TOP1: Light smoke

TOP2: Medium smoke

TOP3: Intensive smoke

Incl. cleaning and service damper

Accessories:

Smoke pipe connection RZ325 for a Turbomat 2 trolleys house

Smoking material: wood chips

Frequency: 50 Hz

Voltage: 230/400 V with N

Dimensions and parameters of the smoke-generator

Dimensions	Unit	RZ325
Width	cm.	32.5
Depth total	cm.	95,0
Height	cm.	135.3
Connected power	kW	1,5
Weight	kg	115,0

2 pcs loading platforms

Pipes for exhaust air: not included in the value