

QUOTATION

FESSMANN TURBOMAT 3000 2W - EL

Combined Universal Smokehouse for thermal treatment of food



Single row system

Capacity for 2 smoke trolleys, batch-type, with following maximum outside dimensions of each trolley: (Width x Length x Height in cm): 104 x 102 x 198 (H) cm;
Maximum length of the smoking stick 100 cm

Control panel: FPc 100



Heating: electric, **56,8 kW**;

Adjustable air circulation

Pneumatically controlled fresh air-, exhaust air- and smoke damper;
cleaning: foam cleaning;

Installation dimensions in cm

Dimensions	Unit	2W EL
Base width	CM.	151
Base depth	CM.	237
Corpus height (without el.motor height and pipes)	CM.	250
Minimum height of the workshop	CM.	304
Recommended height of the workshop	CM.	320
Trolley dimensions HxWxD	CM.	198x104x102 cm

Accessories:

Set of blades made of special steel for the control board with width 325 mm (with smoke-generator RZ325)

Smoke feeding: on the right side

Without after-burning system

Installation on ready made floor;

Voltage: 230/400 V with N

Frequency: 50 Hz

Smoke-generator RZ 325



Smoke generator RZ325 system with 3 smoke densities:

TOP1: Light smoke
TOP2: Medium smoke
TOP3: Intensive smoke
Incl. cleaning and service damper

Accessories:

Smoke pipe connection RZ325 for a Turbomat 2 trolleys house
Smoking material: wood chips
Frequency: 50 Hz
Voltage: 230/400 V with N

Dimensions and parameters of the smoke-generator

Dimensions	Unit	RZ325
Width	cm.	32.5
Depth total	cm.	95,0
Height	cm.	135.3
Connected power	kW	1,5
Weight	kg	115,0

2 pcs loading platforms
