

Gabrovski-Str.81B Zapadna promichlena zona 5000 V.Tarnovo, Bulgarien Tel. 00359/ 62/ 623536 00359/ 62/601372 office@nesto.bg

QUOTATION

TRAYSEALER SEALPAC 610



- Very compact construction
- High flexibility in terms of service and cleaning:

 * Machine can be operated from all sides

 - * Fast and easy cleaning of the tool
 - * Short time for retrofitting

Technical specifications SEALPAC 610

Type: 610

Capacity: up to max. 6-8 cycles /min.

Number of trays per cycle: 1

Connection : 3X400/230V+N+E – Max. 4,5 KW

Air consumption : 8 Bar - 650 L/min

Vacuum pump : not included;

Vacuum consumption : depending on the product weight

approx.100 m³/h.

Water consumption : using a closed system is recommended

Gas consumption : only when performing vacuum / gas, depending on the size

of the trays, dimensions of the tool, the product and the

desired speed

Machine dimensions:

Length: 4 300 mm

Width: 900 mm

Height: 1 950 mm

Specification Product/ Packaging

Product : fresh chilled meat

Packaging : molded trays

Trays material : all materials, susceptible to sealing

(artificial materials, aluminum, cardboard)

Trays dimensions : 325 x 265 x 65 mm. max

Top film : all materials, susceptible to sealing

General requirements for the trays.

- Film and trays to be sealed well, especially in combination Trays to be stable in size and shape Width of sealed edge min. 5 mm

<u>Condition:</u> Second-hand machine, completely overhauled