

QUOTATION

Deep-drawing vacuum-packing machine SEALPAC RE 25



1. Specification

Formats	:	4x3;
Length of drawing	:	447 mm
Depths of drawing	:	max. 50 mm
packing	:	rigid film
bottom film	:	540 mm (+4/+2 mm)
Top film	:	535 mm (+1/-1 mm)
Productivity	:	6 – 8 tacts/min
Dosage	:	no
Gas	:	yes

Voltage	:	3 ph 400V /50Hz, N, I=30 A P=12 kw	
Compressed air	:	min. 6 bar Supplying pipeline 1"	
Water	:	100-150 liters/hour, 15° C max	½" input
Work-shop	:	air-conditioned	

2. Parameters

Machine

- | | |
|------------------|-----------|
| Length | 13 000 mm |
| Width | 1 300 mm |
| Height | 2 000 mm |
| Tools distance - | 6 350 mm |
- 2 x 4- point lifting system
- Transport chain made of stainless steel
 - Forming and vacuum systems
 - Unrolling systems for top and bottom films
 - Electrical and pneumatic control
 - Servicing buttons
 - safety circuit-breakers for water and compressed air
 - magnet circuit-breakers for protective covers
 - With venting system
 - protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting vario

1 taking-out band

4: Pumps

1 vacuum pump 250 m³ - not included in the delivery

5: Tools

Vario-tools

Base tool

Film width	540 mm
Length of drawing	447 mm
Max.depth of drawing	50 mm
Appropriate for rigid films	

Vario 1

4 bands, 3 row, = 12 packings/tact
Packing dimensions :
Form dimensions : L x B = 132.0 x 110.0 mm
Outside dimensions : L x B = 150.0 x 125.0 mm

