

QUOTATION

Deep-drawing vacuum-packing machine HAJEK VS 30 / 320



1. Specification

Formats	:	3x1
Length of drawing	:	197 mm
Depths of drawing	:	max. 80 mm
packing	:	flexible film
bottom film	:	322 mm (+4/+2 mm)
Top film	:	300 mm (+1/-1 mm)
Productivity	:	6 – 8 tacts/min
Voltage	:	3 ph 400V /50Hz, N, P= 8 kw
Compressed air	:	min. 6 bar , 110 l/min
Water	:	100-150 liters/hour, 15° C max.
Work-shop	:	air-conditioned

2. Parameters

Machine

Length	3500 mm
Width	950 mm
Height	1700 mm
Tools distance -	1450 mm
Transport chain made of stainless steel	

- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting

4: Pumps

Busch 100m³

5: Tools

Vario-tools

Base tool

Film width	322 mm
Length of drawing	197 mm
Max.depth of drawing	80 mm
Appropriate for flexible films	

Vario 3

2 bands, 1 row, = 2 packings/tact

Packing dimensions :

Form dimensions : L x B = 185.0 x 84.0 mm

Outside dimensions : L x B = 200.0 x 99.0 mm

