

QUOTATION

Deep-drawing vacuum packing machine TIROMAT COMPACT 420



1. Specification

formats	:	3x2	
length of drawing	:	355 mm	
depth of drawing	:	60 mm	
packing	:	flexible film	
bottom film	:	426 mm (+1/-0 mm)	
top film	:	422 mm (+1/-0 mm)	
Productivity	:	4 -6 tacts	
Voltage	:	400V /50Hz, N,	
Compressed air	:	min. 6 bar	
Water	:	80-100 liters/hour, 15° C max.	½" input
Work-shop	:	air-conditioned	

2. Parameters

Machine

- Length: 9 200 mm
Width : 1 100 mm
Height: 2 000 mm
Tools dimension: 1 250 mm
- Forming and vacuum systems
 - Safety circuit breakers for water and compressed air
 - Magnet circuit breakers for protective covers
 - Protective devices according current standards
 - Made of stainless steel

3. Accessories

- 1 sections transverse cutting
1 section longitudinal cutting rotary knives
Main motor 220 V
1 device for control of printed top film - photocell

4: Tools

Base tool

- Film width 422 mm
Length of drawing 355 mm
Max.depth of drawing 60 mm
For flexible film

Vario 1

- 3 bands, 2 rows = 6 packings/tact
Packing dimensions:
Form dimensions : L x B = 160,0 x 114,0 mm
Outside dimensions : L x B = 177,5 x 131,5 mm



