

QUOTATION

Deep-drawing vacuum-packing machine MULTIVAC R 230



1. Specification

Formats	:	2x1
Length of drawing	:	135 mm
Depths of drawing packing	:	60 mm rigid film
bottom film	:	422 mm (+4/+2 mm)
Top film	:	417 mm (+1/-1 mm)
Productivity	:	8 – 10 tacts
Dosage	:	no
Gas	:	yes
Voltage	:	3 ph 400V /50Hz, N, I=15 A P=6 kw
Compressed air	:	min. 6 bar Supplying pipeline 1"

Water : 100-150 liters/hour, 15° C max ½" input

Work-shop : air-conditioned

2. Parameters

Machine

Length 5200MM

Width 1100MM

Height 2100MM

Tools distance - 1450mm

2 x 4- point lifting system

- Transport chain made of stainless steel
- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting

2 devices for draining out of the wasting stripes

For rigid films

1 taking-out band

4: Pumps

1 vacuum pump 200 m³

5: Tools

Vario-tools

Base tool

Film width 422 mm

Length of drawing 135 mm

Max.depth of drawing 60 mm

Appropriate for rigid films

Vario 1

2 bands, 1 row, = 2 packings/tact

Packing dimensions :

Form dimensions : L x B = 170.0 x 117.0 mm

Outside dimensions : L x B = 190.0 x 133.0 mm

BOTTOM FILM = 422
TOP FILM = 417

