

QUOTATION

Deep-drawing vacuum-packing machine EUROPACK TH 3200- 360



1. Specification

Formats	:	3x1
Length of drawing	:	246 mm
Depths of drawing packing	:	max. 80 mm flexible film
bottom film	:	362 mm (+4/+2 mm)
Top film	:	350 mm (+1/-1 mm)
Productivity	:	4 – 6 tacts/min
Voltage	:	3 ph 400V /50Hz, N, 11A
Compressed air	:	min. 6 bar , 110 l/min
Water	:	100-150 liters/hour, 15° C max.
Work-shop	:	air-conditioned

2. Parameters

Machine

- Length 3250 mm
- Width 800 mm
- Height 1600 mm
- Tools distance - 1220 mm
- Transport chain made of stainless steel
- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

2 section for tranverse cutting

4: Pumps

not included

5: Tools

Base tool

- Film width 362 mm
- Length of drawing 246 mm
- Max.depth of drawing 80 mm
- Appropriate for flexible films

Vario 1

3 bands,1 row, = 3 packings/tact

Packing dimensions :

Form dimensions : L x B = 230.0 x 94.0 mm

Outside dimensions : L x B = 246.0 x 110.0 mm

