

QUOTATION

Deep-drawing vacuum-packing machine KOMET QUICKVAC 2000



1. Specification

Formats	:	2x1
Length of drawing	:	222 mm
Depths of drawing	:	max. 80 mm
packing	:	flexible film
bottom film	:	322 mm (+4/+2 mm)
Top film	:	315 mm (+1/-1 mm)
Productivity	:	5 – 7 tacts/min
Voltage	:	3 ph 400V /50Hz, N, P= 6 kw
Compressed air	:	min. 6 bar , 110 l/min
Water	:	100-150 liters/hour, 15° C max.
Work-shop	:	air-conditioned

2. Parameters

Machine

- Length 2600 mm
- Width 800 mm
- Height 1700 mm
- Tools distance - 1120 mm
- Transport chain made of stainless steel
- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting

4: Pumps

Busch 100m³

5: Tools

Base tool

- Film width 322 mm
- Length of drawing 222 mm
- Max.depth of drawing 80 mm
- Appropriate for flexible films

Vario 1

- 1 bands, 1 row, = 1 packings/tact
- Packing dimensions :
- Form dimensions : L x B = 210.0 x 125.0 mm
- Outside dimensions : L x B = 222.0 x 145.0 mm

