Gabrovski-Str.81B
5000 V.Tarnovo, Bulgarien
Tel. 00359/ 62/ 623536
00359/ 62/ 601372
office@nesto.bg

QUOTATION

Deep-drawing vacuum-packing machine VARIOVAC 2000 VA



1. Specification

Formats	:	1x1
Length of drawing	:	238 mm
Depths of drawing	:	max. 100 mm
packing	:	flexible film , MAP
bottom film	:	355 mm (+4/+2 mm)
Top film	:	345 mm (+1/-1 mm)
Productivity	:	6 – 8 tacts/min
Dosage	:	no
Gas	:	yes
Voltage	:	3 ph 400V /50Hz, N, I=32 A P= 9,7 Kw
Compressed air	:	min. 6 bar , 110 l/min
Water	:	100-150 liters/hour, 15° C max.
Work-shop	:	air-conditioned

2. Parameters

Machine

Length 5 600 mm
Width 950 mm
Height 1 900 mm
Tools distance - 1 770 mm
Transport chain made of stainless steel

- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards
- control panel - new



3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting

1 taking-out band

4: Pumps

Busch 100m³

5: Tools

Base tool

Film width	355 mm
Length of drawing	238 mm
Max.depth of drawing	100 mm
Appropriate for flexible films	

Vario 1

1 bands, 1 row, = 1 packings/tact
Packing dimensions :
Form dimensions : L x B = 300.0 x 223.0 mm
Outside dimensions : L x B = 315.0 x 238.0 mm

