



Gabrovski-Str.81B
Zapadna promichlena zona
5000 V.Tarnovo, Bulgarien
Tel. 00359/ 62/ 623536
00359/ 62/ 601372
office@nesto.bg

QUOTATION

TRAYSEALER MONDINI E 365 VG



The traysealer MONDINI is completely made of special stainless steel. It's appropriate for packing of large amount of products, with or without gas
Standard accessories MONDINI E 365 VG

- Automatic lead-in conveyor
- Trays movement through servomotor



- Sticking sections and temperature adjustment
- Folie movement
- Quick change tool system
- LCD display



- Electrical signalling for folie breaking
- Adjustable mandrel for folie



- Movable output band



Technical specification MONDINI E 365 VG

Connection	: 3X400/230V+N+E – Max. 23,0 KW
Air consumption	: 8 Bar - 650 L/min
Vacuum pump	: red oxygen 300 m³ - not included in the delivery
Gas consumption	: optional for vacuum/gas, depends on trays size, Tool dimensions, product type and required speed
Packings:	moulded trays
Tray dimensions:	190 x 144 mm - 4 pcs / tact
Folie:	approx. 350mm – appropriate for thermal sticking
Productivity *:	approx. 10 - 12 tacts/ minute

* Note: the productivity depends on the following parameters:
product type, chosen packing regime (only sticking or vacuum/gas)
machine adjustment, synchronization with peripheral devices , packing materials.

General tray requirements

- sticking well folie and trays, especially combined
- Trays with consolidated size and shape
- At least 5 mm sticking width of tray edge

Machine dimensions :

Length:	7 000 mm
Width:	1 100 mm
Height:	2 200 mm (2 450 mm when covers open)
Weight:	approx 4 700 kg
