

QUOTATION

TRAYSEALER SEALPAC 750



- Very compact construction
- High flexibility in terms of service and cleaning:
 - * Machine can be operated from all sides
 - * Fast and easy cleaning of the tool
 - * Short time for retrofitting

Technical specifications SEALPAC 750

Type:	750
Capacity:	up to max. 6-8 cycles /min.
Number of trays per cycle:	4
Connection	: 3X400/230V+N+E – Max. 4,5 KW
Air consumption	: 8 Bar - 650 L/min
Vacuum pump	: not included;
Vacuum consumption	: depending on the product weight approx.140 m ³ /h.
Water consumption	: using a closed system is recommended
Gas consumption	: only when performing vacuum / gas, depending on the size of the trays, dimensions of the tool, the product and the desired speed
Machine dimensions:	
Length	: 5000 mm
Width	: 900 mm
Height	: 2000 mm

Specification Product/ Packaging

Packaging	: molded trays
Trays material	: all materials, susceptible to sealing (artificial materials, aluminum, cardboard)
Trays dimensions	: LxB 275/175 mm
Top film	: all materials, susceptible to sealing

General requirements for the trays.

- Film and trays to be sealed well, especially in combination
- Trays to be stable in size and shape
- Width of sealed edge min. 5 mm

Condition:

Second-hand machine, completely overhauled
