

QUOTATION

Deep-drawing vacuum-packing machine MULTIVAC R 230



1. Specification

Formats	:	2x1;
Length of drawing	:	227 mm
Depths of drawing	:	100 mm
packing	:	flexible film
bottom film	:	425 mm (+4/+2 mm)
Top film	:	416 mm (+1/-1 mm)
Productivity	:	6 – 10 tacts
Dosage	:	no
Gas	:	yes
Voltage	:	3 ph 400V /50Hz, N, I=29 A P=11 kw
Compressed air	:	7 ÷ 10 bar, supplying pipeline 3/4" ÷ 1"
Water	:	1,4 ÷ 4,5 bar, 15° C max 1/2" input
Work-shop	:	air-conditioned

2. Parameters

Machine

Length	5500 mm
Width	1050 mm
Height	2000 mm
Tools distance -	2500 mm

- 2 x 4- point lifting system
- Transport chain made of stainless steel
- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting

2 devices for draining out of the wasting stripes

For flexible films

1 taking-out band

4: Pumps

1 vacuum pump 160 m³

5: Tools

Vario-tools

Base tool

Film width	425 mm
Length of drawing	227 mm
Max.depth of drawing	100 mm
Appropriate for flexible films	

Vario 1

3 bands, 1 row, = 3 packings/tact

Packing dimensions :

Form dimensions : L x B = 212.0 x 175.0 mm

Outside dimensions : L x B = 227.0 x 190.0 mm

BOTTOM FILM = 425
TOP FILM = 416

