

QUOTATION

Deep-drawing vacuum-packing machine MULTIVAC R 530



1. Specification

Formats	:	2x1
Length of drawing	:	255 mm
Depths of drawing	:	max. 100 mm
packing	:	flexible film and rigid film
bottom film	:	462 mm (+4/+2 mm)
Top film	:	460 mm (+1/-1 mm)
Productivity	:	6 – 8 tacts/min
Dosage	:	no
Gas	:	yes
Voltage	:	3 ph 400V /50Hz, N, I=32 A P=11 kw
Compressed air	:	min. 6 bar Supplying pipeline 1"

Water : 100-150 liters/hour, 15° C max ½“ input
Work-shop : air-conditioned

2. Parameters

Machine

- Length 6800mm
- Width 1100mm
- Height 2000mm
- Tools distance - 1750mm
- 2 x 4- point lifting system
- Transport chain made of stainless steel
- Forming and vacuum systems
- Unrolling systems for top and bottom films
- Electrical and pneumatic control
- Servicing buttons
- safety circuit-breakers for water and compressed air
- magnet circuit-breakers for protective covers
- With venting system
- protective devices according current standards

3. Accessories

1 section for longitudinal cutting with rotating knives

Knife shafts with rotating knives

1 section for tranverse cutting

For flexible films

1 section for tranverse cutting

For rigid films

1 taking-out band

4: Pumps

Busch

5: Tools

Vario-tools

Base tool

Film width 462 mm
Length of drawing 255 mm
Max.depth of drawing 100 mm
Appropriate for flexible and rigid films

Vario

2 bands, 1 row, = 2 packings/tact

Packing dimensions :

Form dimensions : L x B = 235.0 x 195.0 mm

Outside dimensions : L x B = 254.0 x 210.0 mm

