

## QUOTATION

### VACUUM FILLER VEMAG ROBBY



- Vacuum filler for rectilinear filling
- Continuous working, portioning and hanging regime
- Filling mechanism: with rotary vane pump
- Hopper content: 80 liters; duple-piece
- Build-in vacuum pump with circulation greasing
- Build-in portioning computer PC II



- Portion weight: 5 – 60 000 gr
- Adjustment: up to 1000 gr – 0,1 gr / cycle  
over 1000 gr – 1,0 gr / cycle
- Adjustable reverse suction
- Adjustable pause between portions: from 50 to 6000 msec
- Sleeplessly adjustable filling speed: 0 – 100 %
- Faults indication with service information
- Program memory: 99 programs
- Indications with letters and figures
- Function `copy` for filling programs
- Max. portioning capacity: approx. 500 portions / min depending on type of the wrapper and portion size
- Entering and indication of the product names
- Hydraulic leading with 3-phases motor 4 kW
- Filling pressure – max. 40 bar
- Filling rate: up to 2 700 kg / h
- Working voltage: 400 V 50 Hz

Machine dimensions in cm:

Width: 85, 0

Length: 92, 0

Height: 162, 0

Installed power: 5, 1 kW

Voltage: 400 V, 50 Hz

Weight: 425 kg