

QUOTATION

FESSMANN TURBOMAT T 3000 4W - HD
Combined Universal Smokehouse for thermal treatment of food



Single row system

Capacity for 4 smoke trolleys, batch-type, with following maximum outside dimensions of each trolley: (Width x Length x Height in cm): 104 x 102 x 198 (H) cm

Maximum length of the smoking stick 100 cm

Control panel: MC 2

Heating: High pressure steam 8 bar, 148 kW;
Motor power: 12,0 kW

Adjustable air circulation
Pneumatically controlled fresh air-, exhaust air- and smoke damper
Cleaning: foam cleaning

Cooking and humidification: Low pressure steam 0,5 bar

Installation dimensions in cm

Dimensions	Unit	4 W steam
Base width	cm	151
Base depth	cm	475
Corpus height (without el. motor height and pipes)	cm	250
Minimum height of the workshop	cm	330
Recommended height of the workshop	cm	350
Trolley dimensions HxWxD	cm	198x104x102 cm

Set of blades made of special steel for the control board with width 550 mm (with smoke-generator RZ 550)

Smoke feeding: on the right side
Without after-burning system
Installation on ready made floor
Voltage: 230/400 V with N
Frequency: 50 Hz

Smoke-generator RZ 550



Smoke generator RZ 550 system with 3 smoke densities:

TOP1: Light smoke
TOP2: Medium smoke
TOP3: Intensive smoke
Incl. cleaning and service damper

Accessories:

Smoke pipe connection RZ 550 for a Turbomat 3 trolleys house
Smoking material: wood chips
Frequency: 50 Hz
Voltage: 230/400 V with N

Dimensions and parameters of the smoke-generator

Dimensions	Unit	RZ 550
Width	cm	55,0
Depth total	cm	115,0
Height	cm	159,0
Connected power	kW	1,8
Weight	kg	235,0

2 pcs loading platforms

Pipes for exhaust air: not included in the value
